



## Eko-Therm™ Curtain

...

Our *Eko-Therm™ Curtains* are manufactured from our *Eko-Therm™* material rated to 500°F continuous and intermittent to 3000°F. All edges are folded over and hemmed to provide a reinforced perimeter. All hems and seams are stitched using a high temperature, high tensile thread.

### Worbo Technology

- Leading the way in user friendly thermal safety protection, Worbo's *Eko-Therm™* products are manufactured from flexible mylar aluminized fabrics to provide a unique combination of thermal insulation and heat reflective qualities.
- The ability to reflect radiant and convective heat makes our *Eko-Therm™* Curtain an excellent choice for maintaining cooling process temperatures in high ambient conditions or alongside external radiating heat sources.
- Up to 90% of external heat sources are reflected away from the *Eko-Therm™* Blanket mirror like surface.
- Our *Eko-Therm™* Curtains are easily cut in the field using an ordinary pair of scissors without "end fray" to accommodate valves, brackets, clamps etc.
- Worbo offers a wide variety of hangers and fasteners to facilitate easy removal and re-installation of the *Eko-Therm™ Curtain*. These fasteners include grommets, turned over rod pockets, ¼ turn fasteners, hook and loop (Velcro®), snaps, etc.

### Dimensional Data

Available in virtually any size and dimension.

### Temperature

Rated to 500°F (260°C) continuous, intermittent to 3000°F (1649°C).

### Environmental Resistance

Excellent resistance to ozone, oxidization, UV, corona, cosmic radiation, ionising radiation and weathering in general.

### Flammability

1.0 second flame resistance after flame – ASTM D6413  
13 mm char length – ASTM D6413

### Radiation Reflectivity

15 seconds – MIL-C-24929A

### Breaking Strength

- ... Warp 1780 N – ASTM D5034
- ... Fill 1335 N – ASTM D5034

### Adhesion foil / fabric

No separation



...

[www.worbo.com](http://www.worbo.com)